



4G MiFi Specificationon (4G MIFI规范书)

Category (类别)	Feature & specification (特性和规格)	Description (描述)
Basical Information (基本信息)	Model Name (模型名称)	MPA-C10 (4G MIFI)
	Form Factor (外形)	Mobile WiFi
	Dimension (尺寸)	107*65*10.8mm
	Weight (重量)	约75g
	Color(颜色)	灰色/蓝色/紫色/墨绿色
ID&MD Model (ID和MD模型)	ID	
Air Interface (空中接口)	Technical Standard(技术标准)	Compatible with LTE、802.11 b/g/n/ax (兼容LTE、802.11 b/g/n/ax)
	Frequency (频率)	LTE:1,3,5,8,38,39,40,41 W:1,8
	WIFI6 (无线网络6)	2.4G, WIFI 1*1, 802.11 b/g/n/ax ; channel: 1~13 (2.4G, WIFI 1*1, 802.11 b/g/n/ax通道: 1~13)
Performance (表现)	Maximum Data Throughput(最大数据吞吐量)	LTE CAT 4 LTE 150Mbps/50Mbps
Hardware (硬件)	Receive Diversity (接收分集)	Support Receive Diversity (支持接收分集)
	BB Chipset (BB芯片组)	ZX297520V3T (中芯微)
	RF Chipset (射频芯片组)	ZX234230A (中芯微)
	WiFi Chipset (WiFi芯片组)	AIC 8800DW
	Memory (内存)	256Mb RAM + 64Mb NOR
	USB Charging (USB充电)	above 5V/1A (5V/1A以上)
	Battery (电池)	Li-ion Battery 3000mAh (锂离子电池3000mAh)
	Charging time (充电时间)	<3.5 hours
	Working time (工作时间)	8-9h(3000mAh)
	Standby time (待机时间)	72h(3000mAh)
	LCD/LED	1) Power/Battery Status Indicator 2) 4G/3GNetwork Status Indicator 3) WIFI Indicator 1) 电源/电池状态指示灯 2) 4G/3G网络状态指示灯 3) WIFI指示灯
	USB	Charge & internet (充电和互联网)
Buttons (按钮)	POWER, Reset (电源、复位)	

Software (软件)	UI	WebUI , Mobile WEB UI (WebUI、移动WEB UI)
	SW Update(软件升级)	Local Update, (本地下载工具更新)
	WIFI Mode(wifi模式)	AP
	WIFI Security (wifi安全)	OPEN & WPA2-PSK & WPA-PSK/WPA2-PSK; (开放&WPA2-PSK&WPA-PSK/WPA2-PSK;)
	IPv4	Support(支持) IPv4
	IPv6	Support(支持) IPv6
	Firewall (防火墙)	Mac/IP address filter, Port forwarding, WiFi Black/White list (Mac/IP地址过滤器, 端口转发, WiFi白/黑名单)
	SNTP	Support(支持)
	DMZ	Support(支持)
	HTTP	Support(支持)
Environment (环境)	Operating Temperature (工作温度)	Normal(正常):-10°C to +45°C
	Storage Temperature(储存温度)	-20° C to +70° C
	Humidity(储存湿度)	5%~ 95%
	Mitra Power Solutions Co.,Ltd TEL:0769-83733639 http://www.mitra.cn	